

CoreLite[®] Board

Safety Data Sheet for CoreLite Board

According to OSHA 29 CFR 1910.1200

Last Revised: June 13, 2016

Section 1 Identification

CoreLite Board PVC Foam Core

Recommended Use: Core material for composite sandwich construction

Company Identification: CoreLite
1060 E. 30 St.
Miami, FL 33013 USA
Tel +1 (305) 921-4292
Fax +1 (214) 905-4365

Section 2 Hazards Identification

Polymerized cross-linked aromatic PVC foam (CAS. No. 9002-86-2)
This document is prepared pursuant to the OSHA Hazard Communication Standard (29 CFR 1910.1200). In addition, other substances not "Hazardous" per this OSHA Standard may be listed. Where proprietary ingredient shows, the identity may be made available as provided in this standard.

Section 3 Composition/ Information on Ingredients

Polymerized cross-linked aromatic PVC foam (CAS. No. 9002-86-2)

Section 4 First-Aid Measures

Inhalation	Evacuate individual to an area with fresh air. If difficulty in breathing persists, administer oxygen. If breathing stops or asphyxia is apparent, administer CPR and call for emergency assistance.
Skin Contact	Flush with water or wash with soap and water. Do not blow off dust with compressed air. Seek medical attention if reaction occurs.
Eye Contact	Flush eye, both upper and lower lid, with water. Seek medical attention if irritation persists.
Ingestion	Drink water. If large quantities are ingested and symptoms develop, seek medical attention.

Section 5 Fire-fighting Measures

Hazards:	Under normal circumstances this product will not support the fire and will self extinguish when the fire source is removed, but in the presence of sufficient heat and oxygen it will burn. The probability of dust explosions from PVC dust is very low, however, do not smoke or use naked lights, open flames, space heaters or other ignition sources near rigid foam fabricating operations near sheets. Install foam only after all welding, cutting or other hot work has been completed. If hot work trade must be done after foam has been installed, the hot work trade must be warned. Remove foam from Immediate work area to a sufficient distance that heat transmitted from the torch or through the metal mill not ignites the foam. Remove all combustible material from vicinity of and immediately below work area. Post a fire watcher equipped with a fire extinguisher during and for 30 minutes after hot operations. Stop work immediately if foam begins to smoke and remove more foam from work area. When cutting rigid PVC foam, keep a fire extinguisher nearby. Work should be carried out in well ventilated area-do not breathe fumes.
Extinguishing Media	If stored or in-place PVC foam should ignite, extinguish fire immediately by drenching with water spray from a fire hose. For small fires, use water spray, foam, carbon dioxide, or dry chemical extinguishers.
Protective equipment:	Wear positive pressure self-contained breathing apparatus and protective turnout clothing. Protect all indoor bun and sheet storage areas with fusible sprinklers. Maintain a minimum clearance of six feet between tops of foam and sprinkler heads.

Section 6 Accidental Release Measures

No special measures required

Section 7 Handling and Storage

Handling:	Avoid generation or accumulation of dust. Protective equipment must be used if dust is created. Provide general and/or local exhaust ventilation to control airborne level.
Storage:	Product should be stored in a cool, dry location. Store away from open flame, heat sources or other dangerous sources of ignition.

Section 8 Exposure Controls/Personal Protection

Exposure Limit Values (for particles): **Polymerized cross-linked aromatic PVC foam** (CAS. No. 9002-86-2) TLV not established. MAK: (as dust) 1.5 mg/m³ fixed encoding issue (Respirable fraction); (DFG 2004)

Exposure Controls: Whenever use of the product results in creation of dust, dust collection units (mechanical or vacuum) are recommended to prevent the potential accumulation of airborne dust clouds and to decrease inhalation exposures. In addition, individual use of a dust/mist respirator with NIOSH/MSMA (TC-21C-132) approval, eye protection, gloves, and clothing covering the arms and legs are recommended.

Section 9 Physical and Chemical Properties

Appearance: Rigid cellular plastic

Specific Gravity Variable depending on the application

Section 10 Stability and Reactivity

Stability Stable under normal conditions and working temperatures.

Reactivity Hazardous polymerization will not occur.

Other Dangerous decomposition products include Hydrogen chloride, carbon monoxide, and possible traces of halogen acids and nitrogen oxides evolve under fire conditions.

Section 10 Toxicological Information

Toxicological Tests: None performed

Skin Contact: May cause itching or allergic reaction in sensitive Persons after pro-longed exposure. However, with the appropriate protective equipment, no information available to us suggests that any medical condition might be aggravated by exposure to this product.

Eye Contact: Dust may cause irritation, redness, tearing

Inhalation: Dust may cause irritation of respiratory tract. Inhalation of excessive dust from product can cause asphyxiation due to coating of lung tissue; may cause nasal dryness, irritation and obstruction; coughing, sneezing may occur. Repeated excessive exposures to dusts may cause respiratory irritation and possibly other respiratory effects. In laboratory animals, repeated inhalation exposure to concentrations of 8000 PPM produced no adverse affects; higher concentrations produced only minor biochemical changes such as an increase in cholesterol.

Ingestion: Not likely to occur. No known adverse effects.

Section 12 Ecological Information

Ecotoxicity	No data available
Mobility	Not soluble in water. Keep out of sewage/drainage systems and waterways.
Persistence and degradability	Not biodegradable

Section 13 Disposal Considerations

Disposal should be in accordance with existing federal and local regulations. Incinerate or bury in a approved landfill according to local, state and federal regulations.

Section 14 Transport information

Road	No restrictions
Rail	No restrictions
Air	No restrictions
Sea	No restrictions

Section 15 Regulatory Information

U.S. Toxic Substances Control Act (TSCA): PVC is listed.

Section 16 Other information

The information contained herein is based on data considered to be accurate. While the information is believed to be reliable, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Since the use of this information and the conditions and use of this product are controlled by the user, it is the user's obligation to determine the conditions for safe use of this product.

Asia
2/F Leader CTR 37 Wong Chuk
Hang Rd Aberdeen
Hong Kong
T +852 8193 3434

North America
1060 E. 30 St.
Miami, FL 33013
USA
T +1 (305) 921-4292

South America
Km. 24 Via Daule
Guayaquil
Ecuador
T +593 4-226-7008

Europe
Via Enrico Fermi, 170
46011 – Acquanegra s/C (MN)
Italy
T +39 3398 107391