

Certificate No: **TAK000025F** 

# TYPE APPROVAL CERTIFICATE

This is to certify:	
That the Sandwich Core Materials	
with type designation(s) CoreLite® PVC F	
CORELITE ITALIA S.r.I. Acquanegra sul Chiese, MN, Italy	
is found to comply with DNV class programme DNV-CP-0084 – Type approval – San	dwich core materials
Application:	
Manufacturing of sandwich structured composites.	
Product(s) approved by this certificate is/are accepted for ins	stallation on all vessels classed by DNV.
Issued at <b>Høvik</b> on <b>2022-09-22</b> This Certificate is valid until <b>2027-09-21</b> .	for <b>DNV</b>
DNV local station: Italy/Malta CMC	
Approval Engineer: Gisle Hersvik	
	Gustav Heiberg
	Head of Section

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.



Form code: TA 251 Revision: 2021-03 www.dnv.com Page 1 of 2

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.



Job Id: 262.1-038252-1 Certificate No: **TAK000025F** 

## **Product description**

CoreLite® PVC F: A cross-linked, closed-cell PVC (PolyVinyl Chloride)-foam core material for sandwich construction.

#### Approved variants:

- CoreLite® PVC F 60
- CoreLite® PVC F 80
- CoreLite® PVC F 100
- CoreLite® PVC F 130

#### **Material Properties:**

Variant	Nominal Density (1)	Density Range (1)	Compr. Strength (2)	Compr. Modulus (2)	Shear Strength (3)	Shear Modulus (3)	Elongation at Peak (4)	HRT (5)	Tensile Strength (6)	Tensile Modulus (6)
PVC F 60	60	54 - 69	0.77 (0.53)	58 (40)	0.77 (0.50)	19 (14)	39	n.a.	1.45 (1.20)	52 (40)
PVD F 80	80	72 – 92	1.31 (0.84)	91 (59)	1.06 (0.80)	25 (16)	51	n.a.	1.83 (1.50)	69 (50)
PVC F 100	100	90 – 115	1.70 (1.00)	103 (70)	1.60 (1.00)	39 (24)	49	n.a.	2.00 (1.70)	87 (70)
PVC F 130	130	120 - 150	2.42 (1.80)	150 (110)	1.99 (1.50)	47 (33)	52	47	3.14 (2.70)	121 (100)

All values are average values and verified by testing. The values within brackets are manufacturer specified minimum values (msmv).

## Application/Limitation

The foam complies with the applicable requirements of DNV and is compatible to the laminating resin and/or adhesive.

Any significant changes in design and / or quality of the material will render the approval invalid.

#### Type Approval documentation

## **Tests carried out**

Type Testing carried out in accordance with Type Approval documentation.

## Marking of product

Product/package shall be marked with manufacturer's name and type designation, as well as Item id., Quantity, Production order no., Lot no. and Batch no.

The marking is to be carried out in such a way that it is visible, legible and indelible. The marking of product is to enable traceability to the DNV Type Approval Certificate.

#### Periodical assessment

The scope of the Periodical Assessment is to verify that the conditions stipulated for the Type Approval is complied with and that no alterations are made to the product design or choice of materials.

Periodical assessments (for Certificate Retention / Certificate Renewal) shall be performed according to DNV-CP-0338.

This certificate is only valid if required Periodical assessments are carried out with satisfactory results. To check the validity of this certificate, please look it up in https://approvalfinder.dnv.com

**END OF CERTIFICATE** 

Form code: TA 251 Revision: 2021-03 www.dnv.com Page 2 of 2

<sup>(1)</sup> Density according to ASTM D1622 in kg/m³
(2) Compressive properties according to ASTM D1621-10, procedure B in MPa.
(3) Shear properties according to ASTM C273 in MPa.
(4) Shear elongation at break according to ASTM C273 in %.
(5) Tensile properties according to ASTM D1623 in MPa.

<sup>(6)</sup> Heat Resistance Temperature (HRT) in °C where the shear strength is > 80% of the shear strength at RT. HRT = 47°C.